

TECHNICAL SPECIFICATIONS CD1	600	900
Hexagonal brush's spindle	1	1
Rotation speed of the brush	300-1100	300-1100
Height of work	Variabile	Variabile
Max. height of work	200 mm	200 mm
Width of work	635 mm	935 mm
Main motor	2,2 kW	3 kW
Conveyor motor	0,37	0,37
Conveyor speed	1,5-6 m/min	1,5-6 m/min
Dust collection duct, diameter	90 mm	90 mm
Dimensions	1057 x 1209 x 1160	1057 x 1509 x 1160
Weight	360 Kg	470 Kg

QuickWood



CD1

600-900

Compact and economical brushing machine with a quick change brush system, with high grip conveyor belt.

For a perfect sanding and distressing.



APPLICATIONS

- Wood and sealer sanding
- Designed also for a deep rustic finish.
- Metal Surface Finish

CHARACTERISTICS

- The rotation speed of the brush and the conveyor belt are controlled by inverter
- The top pressure system consists of a rubber pressure rollers, self-adjusting in height
- Reversible sanding brush and feed belt direction
- Quick change Brush system
- The brush height is manually adjustable in height from 0mm to 200mm

ADVANTAGES

- The machine can be equipped with all the Quickwood brushes and the solid wheels for rustic work
- Reduced dimensions
- Value - low cost solution

